



VRF  
Indoor units

Airwell

# XVVA Console



RCV03  
included

## + PRODUCT

- RCV03 remote control included
- DC Inverter centrifugal fan
- Compact unit
- Bidirectional airflow
- Dry contact available



RWV05  
(optional)

## FEATURES

### TECHNOLOGY



ELECTRONIC  
EXPANSION VALVE

### FUNCTIONS USERS



I FEEL



SUPER QUIET



PROGRAMMABLE  
TIMER



AUTO RESTART  
(MEMORY)

### INSTALLER FUNCTIONS



DRY CONTACT  
ON/OFF

### THE + “SUSTAINABLE DEVELOPMENT”

- > Energy savings (mode locking, setpoint limits).

### THE + “USER”

- > New simple and elegant design.
- > Super-quiet unit.
- > Upward and downward blowing for greater comfort.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

### THE + “INSTALLER”

- > Very compact.
- > Ideal solution for rooms with low ceilings.

### THE + “TECHNOLOGY”

- > Optimal regulation thanks to its electronic expansion valve.

## TECHNICAL DATA

INDOOR UNIT	XVVA-050/035/025N-01M22				
Part number	7VF070001				
Phase	Single phase				
RATED POWER					
Cooling mode	kBtu/h	9,50	12,30	15,30	17,00
	<b>kW</b>	<b>2,80</b>	<b>3,60</b>	<b>4,50</b>	<b>5,00</b>
Heating mode	kBtu/h	10,90	13,60	17,00	18,50
	<b>kW</b>	<b>3,20</b>	<b>4,00</b>	<b>5,00</b>	<b>5,50</b>
ELECTRICAL PARAMETERS					
Phase/Voltage/Frequency	1P/220-230V/50-60Hz				
PERFORMANCES					
Airflow (TPV/LS/MS/HS/TCV)	m <sup>3</sup> /h	270/310/390/ 460/540	270/350/420/ 500/580	270/390/460/540/620	
Sound pressure (TPV/LS/MS/HS/TCV)	dB(A)	30/33/38/42/45/42	30/36/40/44/47	30/38/42/45/48	
Sound power level (TPV/LS/MS/HS/TCV)	dB(A)	45/48/52/55/58	47/51/54/57/60	42/48/55/58/61	
INSTALLATION					
Outline dimensions (WxHxD)	mm	700x600x210			
Package dimensions (WxHxD)	mm	783x695x303			
Net weight/Gross weight	kg	15.2/18.7			
Liquid pipe diameter	inches	1/4"			
Suction pipe diameter	inches	1/2"			