

FCF

Floor ceiling monosplit Fixed speed

- Floor ceiling line available in capacities of 12.80 and 15.60 kW.
- Cooling and heating operation mode.
- "I Feel" function with precise room temperature control.



FCF

Floor ceiling monosplit / Fixed speed

[PRODUCT ADVANTAGES]

- 2 directions airflow control.
- Vertical or horizontal installation.

[TECHNICAL DATA]

Indoor units		AWSI-FCF048-N11	AWSI-FCF060-N11
Outdoor units 3~400V - 50 Hz - N		AWAU-YOF048-H13	AWAU-YOF060-H13
COOLING			
Rated capacity	kW	12.8	15.6
Rated power input	kW	4.7	5.51
EER/Energy label		2.72/D	2.83/C
Operating limits	°C	18°/43° Dry bulb	
HEATING			
Rated capacity	kW	14.2	17
Rated power input	kW	4.89	5.52
COP/Energy label		2.90/D	3.08/D
Operating limits	°C	-7°/24° Dry bulb	
INDOOR UNIT			
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	50/53/56	51/54/57
Sound power level	dB(A)	66	67
Airflow (LS/MS/HS)	m³/h	1650/1800/1950	1700/1900/2300
Dehumidification	l/h	4.3	5
Outline dimensions (WxHxD)	mm	1285x675x235	1650x675x235
Package dimensions (WxHxD)	mm	1360x755x313	1725x755x313
Net weight/Gross weight	kg	30/35	40/46
Part number		7SP012213	7SP012218
OUTDOOR UNIT			
Sound pressure level to 1 m	dB(A)	62	63
Sound power level	dB(A)	72	73
Airflow	m³/h	7200	7500
Compressor type		Scroll	Scroll
Outline dimensions (WxHxD)	mm	938x1369x392	938x1369x392
Package dimensions (WxHxD)	mm	1095x1505x495	1095x1505x495
Net weight/Gross weight	kg	110/124	111.1/125.4
Part number 3~400V - 50 Hz - N		7SP062848	7SP062849
POWER SUPPLY 3~400V - 50 HZ - N			
Power supply side		Indoor & Outdoor	Indoor & Outdoor
Power cable section	mm²	3x1.0+5x2.5	3x1.0+5x2.5
Fuse rating am	A	16 + 20	16 + 20
Electrical connections	mm²	3x0.5	3x0.5
PIPE LINE			
Suction pipe diameter	inches	3/4"	3/4"
Liquid pipe diameter	inches	3/8"	3/8"
Max length	m	50	50
Max height	m	25	25

Until end of stock.