XBD CONSOLE DUAL FLOW
MONO & MULTISPLIT

Airwell
Just feel well

NEW

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

A++

Only XBD 012

- → "I Feel" function with precise room temperature control.
- → Airflow direction control, up or down for comfort selection.
- → Easy maintenance.
- → Ideal solution for replacement of electric heaters: best comfort and save money.

PRODUCTS

- Dual flow.
- Operating down to -15°C in cooling and heating mode.
- 4 air outlet direction.
- Compact.
- Mono & multi application.

RC08C

RCW8
(optional)

2 AIR OUTLET WAYS

FEATURES

COMBINATIONS

Indoor unit	Compatible with outdoor unit	
Console	Monosplit	Multisplit
XBD 12	YMD	YCZ
XBD 9X & XAD18X		YCZ

XBD
Console dual flow mono & multisplit

XBD TECHNICAL DATA

		ONLY MULTI CONFIGURATION	Only XBD 012	ONLY MULTI CONFIGURATION
Indoor units		**AWSI-XBD009X-N11**	**AWSI-XBD012-N11**	**AWSI-XAD018X-N11**
Outdoor units			**AWAU-YMD012-H11**	
COOLING				
Rated power	**kW**	**2.6 (0.8-3.3)**	**3.5 (0.8-4.4)**	**4.7 (1.4~5.4)**
Pdesignc	**kW**		**3.5**	
Rated power input	kW		0.992	
SEER/Energy label			**6.7/A++**	
Operating limits	°C		-15°/50° Dry bulb	
HEATING				
Rated power	**kW**	**2.9 (0.85-3.7)**	**3.8 (0.85-5.0)**	**5 (1.4~5.8)**
Pdesignh (average climate)	**kW**		**3.6**	
Pdesignh (warmer climate)	**kW**		**3.6**	
Rated power input	kW		0.995	
SCOP/Energy label (average climate)			4.0/A+	
SCOP/Energy label (warmer climate)			**5.1/A+++**	
Operating limits	°C		-15°/24° Dry bulb	
INDOOR UNIT				
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	35/40/45	36/40/44	39/44/48
Sound power level	dB(A)	56	58	59
Airflow (LS/MS/HS/SS)	m³/h	450/580/680	360/470/550	520/650/740/820
Dehumidification	l/h		1,5	
Outline dimensions (WxHxD)	mm	700x600x210	700x600x210	700x600x210
Package dimensions (WxHxD)	mm	810x305x710	810x305x710	810x305x710
Net weight/Gross weight	kg	13.5/18	15/20	15/20
Part number		**7SP071406X**	**7SP071407**	**7SP071405X**
OUTDOOR UNIT				
Sound pressure level to 1 m	dB(A)		54	
Sound power level	dB(A)		61	
Airflow	m³/h		2000	
Compressor type			Rotary DC Inverter	
Refrigerant type/Ammount	kg		R410a/1.38	
Outline dimensions (WxHxD)	mm		800x554x333	
Package dimensions (WxHxD)	mm		920x615x390	
Net weight/Gross weight	kg		34.5/37.3	
Part number			**7SP062891**	
POWER SUPPLY 1~230V - 50 HZ				
Power supply side		Outdoor	Outdoor	Indoor & Outdoor
Power cable section	mm²		3x1.5	
Fuse rating am	A		16	
Electrical connections	mm²	4x1.0	4x1.0	3x0.5
PIPE LINE				
Suction pipe diameter	inches	3/8”	3/8”	1/2”
Liquid pipe diameter	inches	1/4”	1/4”	1/4”
Max. length	m		25	
Max. height	m		10	

XBD GB 0317 - AIRWELL RESIDENTIAL SAS - Specifications subject to change without notice. Pictures non contractual. Printed in UE.

3, AVENUE DU CENTRE - LES QUADRANTS - BAT. A - 78280 GUYANCOURT, FRANCE
TEL: +33 (0)1 76 21 82 00 - FAX: +33 (0)1 76 21 82 01 - www.airwell-residential.com

Airwell
AIR CONDITIONING & HEATING