

SXT (Telecom)

Floor ceiling
Fixed speed

- Floor ceiling line available in capacities 5.2 and 8.3 kW.
- Operating range -10 up to 46°C in cooling.
- Cooling only operation mode.
- Wireless remote control included, with option of wired control.
- Available in 3PH in 8,3 kW capacity.



RC08B

SXT (Telecom)

Floor ceiling / Fixed speed

[PRODUCT ADVANTAGES]

- **Dedicated product for IT rooms.**
- Treatment of corrosion on outdoor units and electronic cards.
- Wide operating temperature, dedicated product for communication rooms.
- High pressure and low pressure protection.
- Alarm output (dry contact).
- 2D motorized air control.
- Special product design to operate in high humidity and corrosion areas.
- Possibility to reverse dry contact: normally open / normally closed.

[TECHNICAL DATA]

Indoor units		AWSI-SXT018-N11	AWSI-SXT030-N11
Outdoor units 1-230V - 50 Hz		AWAU-YHF018-H11	-
Outdoor units 3-400V - 50 Hz		-	GC 30T LT AW
COOLING			
Rated capacity	kW	5.2	8.3
Pdesignc	kW	5.2	8.3
Input power	kW	1.73	2.77
SEER/Energy label		3.2/E	3.4/E
Operating limits	°C	-10°/46° Dry bulb	
INDOOR UNIT			
Sound pressure level to 1 m (LS/MS/MS)	dB(A)	41/46/52	45/49/54
Sound power level (LS/MS/HS)	dB(A)	62	64
Airflow (LS/MS/HS)	m³/h	900/1050/1300	1250/1400/1750
Dehumidification	l/h	1.9	2.5
Outline dimensions (WxHxD)	mm	1068x675x235	1285x675x235
Package dimensions (WxHxD)	mm	1145x755x313	1360x755x313
Net weight/Gross weight	kg	24/29	29/36
Part number		7SP012226	7SP012229
OUTDOOR UNIT			
Sound pressure level to 1 m	dB(A)	60	61
Sound power level	dB(A)	68	69
Airflow	m³/h	2950	3100
Compressor type		Rotary	Rotary
Outline dimensions (WxHxD)	mm	900x700x340	900x860x340
Package dimensions (WxHxD)	mm	985x730x435	985x905x435
Net weight/Gross weight	kg	50/53	78/82
Part number 1~230V - 50 Hz		7SP061894	-
Part number 3~400V - 50 Hz		-	7SP061713
POWER SUPPLY 1~230V - 50 HZ			
Power supply side		Indoor & Outdoor	-
Power cable section	mm²	5x2.5	-
Fuse rating	A	16	-
Electrical connections	mm²	4x2.5 + 5x2.5	-
POWER SUPPLY 3~400V - 50 HZ			
Power supply side		-	Outdoor
Power cable section	mm²	-	5x2.5
Fuse rating am	A	-	3x16
Electrical connections	mm²	-	5x1.5 + 2x0.5
PIPE LINE			
Suction pipe diameter	inches	1/2”	5/8”
Liquid pipe diameter	inches	1/4”	3/8”
Max length	m	15	30
Max height	m	7	15
Connexion kit - 5 m - without cable	part number	7ACFH0771	7ACFH0771